



# OMNIKEY® 5127CK Mini Reader Board



## EMBEDDED CCID AND KEYBOARD WEDGE RFID READER BOARD

- **Multi-Interface Support** – CCID, Keyboard Wedge and UART interfaces offer flexible integration options for a wide range of applications.
- **Dual frequency and mobile access** – Simultaneously supports low and high frequency credentials, including iCLASS Seos®, HID Prox®, iCLASS SE®, MIFARE® Classic and MIFARE DESFire® EV1; supports NFC and Bluetooth for mobile devices.
- **Compact design** – Very small footprint provides capability for installation in space-constrained designs.
- **Industrial Housed Option** – Rugged case providing protection in the embedded environment.

### Mobile Enabled Reader Features

- Adjustable read settings control overall power and read range of Mobile IDs, enabling flexibility for both close-proximity “tap” and long-range “Twist and Go” distances
- Read settings administered using mobile phone during installation
- Directional antenna enables long-range reading distances up to 2m’ in correct orientation in front of the reader and not behind it

HID Global’s OMNIKEY 5127 Mini reader board opens market opportunities for system integrators seeking simple integration and development of readers using standard interfaces such as CCID, UART or Keyboard Wedge.

The new 5127CK Mini reader board complements the existing 5127CK reader board and 5427CK reader by providing a very compact design for installation in space-constrained solutions.

The CCID interface enables integrators to design finished readers without the need to install or maintain drivers, eliminating complex software lifecycle management issues in the field and accelerating introduction of finished devices in the market.

With the Keyboard Wedge functionality, the reader can retrieve data from a card that is presented to the reader and directly input the card data into an application using keystroke emulation. This eliminates the need for customers to manually enter the card data into an application.

The OMNIKEY 5127CK Mini reader board offers the market-proven OMNIKEY reader feature set and supports low and high frequency technology within a single device. It also supports the latest mobile access solutions via NFC or Bluetooth Smart.

Key features of the OMNIKEY 5127CK reader board include support for the most common low and high frequency card technologies, including Seos, iCLASS, MIFARE and HID Prox. It also includes an integrated management tool that enables field updates to readers for new firmware or changing configuration settings.

For quick and easy integration, HID Global provides an OMNIKEY 5127CK reader board Developer Tool Kit (DTK). The DTK provides the necessary tools, documentation and developer resources material to shorten integration cycles and speed time to market with finished products.

For further information please visit the Developer Center: [hidglobal.com/main/developers/omnikey-5127-ck/](http://hidglobal.com/main/developers/omnikey-5127-ck/)

### CCID Support

- Native CCID implementation supporting Windows®, LINUX® and Mac® operating systems

### Keyboard Wedge

- Fully configurable and programmable keyboard wedge functionality featuring an integrated management console
- Flexible configuration of data structures and output modes

### UART

- Fully featured serial protocol allowing low level integration into host applications
- Autonomous credential processing with card data sent directly over the serial interface

### Broad Credential Support

- NFC and Bluetooth support for Mobile devices
- Dual frequency functionality allowing support for both low and high frequency credentials simultaneously
- HID Prox®, Indala® & EM Prox, MIFARE® Classic, MIFARE® DESFire® EV1, iCLASS®, iCLASS SE®, iCLASS® Seos®, iCLASS Elite®, and other SIO enabled credentials

### Enhanced Lifecycle Management

- Easy firmware updates and configuration setting utilizing a Web interface, SNMP messages and configuration cards
- Developer Tool Kit (DTK) available that contains product samples, development documentation, sample code and access to HID's developer portal

## SPECIFICATIONS



<b>Base Model Number</b>	OMNIEKEY 5127CK Mini	
<b>Dimensions</b>	Reader Board: 50 x 35 x 8.94mm (1.96" x 1.38" x 0.35") Industrial Housing: 55 x 40 x 16mm (2.2" x 1.6" x 0.63")	
<b>Weight</b>	Reader Board: 10.5g (0.4 oz) Industrial Housing: 24.4g (0.9oz)	
<b>Power Supply</b>	Bus powered	
<b>Current Requirements</b>	Base Power consumption (RF interface deactivated) - Average 60mA HF, Prox, amd BLE activated - Average 134mA, Peak 220mA HF polling only - Average 84mA, Peak 160mA Prox polling only - Average 73mA, Peak 130mA BLE advertisement only - Average 60mA, Peak 75mA	
<b>Operating Temperature</b>	32° - 158° F (0° - 70° C)	
<b>Operating Humidity</b>	10 - 90% Relative Humidity	
<b>Storage Temperature</b>	-4° - 176° F (-20° to 80° C)	
<b>HOST INTERFACE</b>		
<b>Host Interface</b>	USB 2.0 (also compliant with USB 1.1)	
<b>Transmission Speed</b>	12 Mbps (USB 2.0 full speed)	
<b>CONTACTLESS SMART CARD INTERFACE</b>	<b>CCID</b>	<b>KEYBOARD WEDGE</b>
<b>Card &amp; Protocols High Frequency</b>	iCLASS, iCLASS SE/SR, iCLASS Seos MIFARE Classic 1K / 4K, Ultra Light, Ultra Light C, Plus, MIFARE DESFire 0.6, MIFARE DESFire EV1, MIFARE SE, DESFire EV1 SE, T=CL, ISO 14443A, ISO14443B CSN, FeliCa, SmartMX with up to 848 kbps transmission rate (depending on card1), ISO 15693 with up to 26 kbps transmission rate (depending on card)	The following credentials can be handled autonomously: iCLASS, iCLASS SE/SR, iCLASS Seos®, MIFARE SE, DESFire EV1 SE, MIFARE Classic 1K / 4K, Ultra Light, Ultra Light C, Plus (Security Lvl 1) , MIFARE DESFire 0.6, MIFARE DESFire EV1 (MAC / DES/3DES / 3K3DES / AES), CEPAS (CAN), FeliCa (Idm), PIV, ISO14443B (CSN)
<b>Cards &amp; Protocols Low Frequency</b>	HID PROX®, Indala Prox, EM Prox, AWID Prox	
<b>Supported API's</b>	PC/SC (ready for 2.01/ CCID mode)	Human Interface Device
<b>PC/SC Driver Support</b>	Compliant with native OS CCID drivers (in CCID mode) HID proprietary PC/SC drivers available for: Windows® XP / Vista™ / 7 (32 bit / 64 bit) / 8, 2003 Server, 2008 R2 Server, Linux (32 / 64 bit, incl. Debian 6.0, Fedora 15, OpenSUSE 11.4, Ubuntu 11.04) & Mac OS X (10.5 Leopard and higher, Intel 32 / 64 bit)	Compliant with native Human Interface Drivers
<b>Status Indicators</b>	Reader Board: Dual color LED (Green=ready, Red=busy) Industrial Housing: Buzzer (Programmable)	
<b>Connectors</b>	Micro USB connector (cable not included) Pico Blade Connector (UART Interface)	
<b>Optional Accessories</b>	Cable Management Kit	
<b>Approvals/Environmental</b>	Compliant to ROHS/REACH, WEEE, IEC 60950-1, CE, FCC Modular, IC (Canada)	
<b>Warranty</b>	Two year manufacturer's warranty	

### ASSA ABLOY

An ASSA ABLOY Group brand

© 2013-2016 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, iCLASS, iCLASS SE, iCLASS Seos, HID PROX and OMNIEKEY are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2016-02-10-ok-5127ck-mini-rdr-brd-ds-en  
PLT-02675

North America: +1 512 776 9000  
Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 5081 1650